

950/3

04 Oct - 2023

CALL FOR QUOTATION

Sir/Madam,

1. Sealed quotation are invited from firm/supplier for procurement of the following items or ARMY PUBLIC SCHOOL MIRAN SAHIB:-

| S.no | Nomenclature | Specifications | Qty |
|------|---|--|-----|
| 01 | 2000-WATT 12-INCH 2-WAY POWERED LOUDSPEAKER | a) Output Power: 2000 W peak (1300 LF + 700 HF) 1000 W continuous RMS (650 LF + 350 HF) b) LF Driver: 12-inch (305 mm) LF driver, 3-inch (76 mm) high-temperature voice coil c) HF Driver: 1.4-inch (35 mm) neodymium magnet HF driver with precision wave guide d) Crossover: 2 kHz e) Maximum SPL: 131 dB peak, 128 dB continuous (dB SPL @ 1 m) f) Frequency Response: 53 Hz – 20 kHz (+/- 3 dB) g) Frequency Range: 46 Hz – 22 kHz (-10 dB) h) Horn Coverage: 90° H x 60° V nominal i) Equalization: Contour Switch Low and High Frequency +3dB Boost j) Connectors: (2) XLR/TRS 1/4" (6.35 mm) combo inputs, (1) XLR link output, (1) IEC power cable input k) Controls: (2) Volume, Power on/off switch, Contour switch, Ground-Lift switch l) Indicators: 2 x Power LED (front and rear), Clip limiter LED m) Protection: Electronic clip, Thermal and transducer overdrive protection n) Power Connection: IEC with Mains Fuse o) AC Voltage Input: 100,110-120,220-240 V, 50/60 Hz p) Enclosure: Trapezoidal, injection-molded, polypropylene enclosure, with perforated steel grille q) Mounting/Installation: 36 mm standard pole mount, Wall or ceiling mount using TSB125 bracket, Flown application with integral M10 suspension points, Wedge monitor r) Dimensions: (H x W x D): 23.8" x 13.9" x 13.8" / 605mm x 354mm x 350mm s) Net Weight: 35.9 lbs. / 16.3 kg. t) Design Origin: Designed and tuned in the USA u) Accessories: TSB125 Bracket, TS212 Cover | 2 |
| 02 | Mixing Console MG Series - MG10X | a) 10-Channel Mixing Console: Max. 4 Mic / 10 Line Inputs (4 mono + 3 stereo) / 1 Stereo Bus / 1 AUX (incl. FX) b) 10-Channel Mixing Console c) Max. 4 Mic / 10 Line Inputs (4 mono + 3 stereo) d) 1 Stereo Bus e) 1 AUX (incl. FX) f) "D-PRE" mic preamps with an inverted Darlington circuit g) 1-Knob compressors | 1 |

Note: Validation of Quotation is for 6 Months.


Jas Sharma
Principal
Army Public School
Miran Sahib, Jammu

| | | | |
|----|--------------------------------------|--|---|
| | | <p>h) High-grade effects: SPX with 24 programs</p> <p>i) 24-bit / 192kHz 2in / 2out USB Audio functions</p> <p>j) Works with the iPad (2 or later) through the Apple iPad Camera Connection Kit / Lightning to USB Camera Adapter</p> <p>k) Includes Cubase AI DAW software download version</p> <p>l) PAD switch on mono inputs</p> <p>m) +48V phantom power</p> <p>n) XLR balanced outputs</p> <p>o) Metal chassis</p> <p>p) Dimensions(W×H×D): 244 mm x 71 mm x 294 mm (9.6"x 2.8"x 11.6")</p> <p>q) Net Weight: 2.1 kg (4.63 lbs.)</p> | |
| 03 | Universal Speaker Stand Mount Holder | Universal Speaker Stand Mount Holder Heavy Duty Tripod adjustable Height from 40" to 71" and 35mm Compatible Insert Easy Mobility Safety Pin and Knob Tension Locking for Stability | 2 |
| 04 | Projector Tripod Stand | Projector Tripod Stand, Laptop stand, Adjustable Height, Perfect for Multi-Purpose stand for Projector, Home, Stage or Studio, Office, Black | 1 |
| 05 | wireless microphone | <p>Elegant high performance dual channel wireless microphone available in eight pairs of frequencies</p> <p>Separate vol control for both channels on the front panel of the receiver</p> <p>Two handheld dynamic transmitters, each operating on 2 × 1.5V AA pencil cells</p> <p>Separate balanced audio output from each channel and an unbalanced mixed output available from the receiver</p> <p>Receiver operates on 12V DC through an AC adaptor</p> | 2 |

2. You are requested to forward your quotation along with GST to reach this office by **20 - Oct - 2023**. The address and contact No for sending the quotations or seeking clarifications for above mentioned item are given below:

- (a) Address: **ARMY PUBLIC SCHOOL, MIRAN SAHIB, JAMMU 181101**
- (b) Contact No: **01923295332**
- (c) Email id: apsmiransahib@awesindia.edu.in

Location of Tender Box: Main Gate 162 Inf Brig Miran Sahib, 181101, Jammu , Jammu and Kashmir


Principal
Army Public School
Miran Sahib, Jammu

Note: Validation of Quotation is for 6 Months.



950/3

Oct - 2023

CALL FOR QUOTATION


Sir/Madam,

1. Sealed quotation are invited from firm/supplier for procurement of the following items or ARMY PUBLIC SCHOOL MIRAN SAHIB:-

| S.no | Nomenclature | Specifications | Qty |
|----------|-----------------------|---|-----|
| 01 | Type 1 Plastic Chairs | <ul style="list-style-type: none">Weight Bearing Capacity : 125 KgDimensions Width (cm) 54 Depth (cm) 54 Height (cm) 75 Weight (Kg) 2 Seating Height (cm)Seating Capacity : 1Warranty Summary: 12 months domestic warranty. We will provide replacement of particular damaged parts only or entire product in case of non availability of damaged partsMaterial: PlasticColor: Pear Wood | 100 |
| 02 | Type 2 Chairs | <ul style="list-style-type: none">Dimensions Width (cm) 57 Depth (cm) 57 Height (cm) 66 Weight (Kg) 16 Seating Height (cm)Primary Material: FabricColor : Cushion Color Blue, Rest BlackWarranty: 12 months domestic warranty... We will provide . replacement of particular damaged parts only or entire product in case of non availability of damaged parts | 25 |
| Pictures | | | |
| 01 | Type 1 Plastic Chairs |  | |
| 02 | Type 2 Chairs |  | |


2. You are requested to forward your quotation along with GST to reach this office by 20 - Oct - 2023. The address and contact No for sending the quotations or seeking clarifications for above mentioned item are given below:

Note: Validation of Quotation is for 6 Months.


Principal
Army Public School
Miran Sahib, Jammu

- (a) Address: ARMY PUBLIC SCHOOL, MIRAN SAHIB, JAMMU 181101
(b) Contact No: 01923295332
(c) Email id: apsmiransahib@awesindia.edu.in

Location of Tender Box: Main Gate 162 Inf Brig Miran Sahib, 181101, Jammu , Jammu and Kashmir


Principal
Army Public School
Miran Sahib, Jammu

Note: Validation of Quotation is for 6 Months.

950/3

04 Oct - 2023


CALL FOR QUOTATION

Sir/Madam,

1. Sealed quotation are invited from firm/supplier for procurement of the following items or ARMY PUBLIC SCHOOL MIRAN SAHIB:-

| S.no | Nomenclature | Specifications | Qty | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--------------------------|--|--|-------------|-------------------|--------------------------|-------|-----------|------|--------------|----------|------|-------------------------------------|------------------|--------|--------------|--------|--------------|-----|-----------------|----------------|-----------------|--------------------------------|------|---------|------------|---|---------------------|-------------------|------|-----------------------|--------------------|---|------------------|--|----------|---|--------------------|--|----|
| 01 | Mirror less Digital Camera with RF-S18-150mm Kit Lens | <table border="1"> <tr> <td>Form Factor</td> <td>DSLR, Mirror less</td> </tr> <tr> <td>Video Capture Resolution</td> <td>2160p</td> </tr> <tr> <td>Lens Type</td> <td>Zoom</td> </tr> <tr> <td>Camera Flash</td> <td>Built-In</td> </tr> <tr> <td>Type</td> <td>Approx. 22.3 × 14.9 mm (APS-C) CMOS</td> </tr> <tr> <td>Effective Pixels</td> <td>24.2MP</td> </tr> <tr> <td>Total Pixels</td> <td>25.5MP</td> </tr> <tr> <td>Aspect Ratio</td> <td>3:2</td> </tr> <tr> <td>Low-Pass Filter</td> <td>Built-in/Fixed</td> </tr> <tr> <td>Sensor Cleaning</td> <td>EOS integrated cleaning system</td> </tr> <tr> <td>Type</td> <td>DIGIC X</td> </tr> <tr> <td>Lens Mount</td> <td>RF (natively supporting RF and RF-S lenses) EF and EF-S lenses can be attached using Mount Adapter EF-EOS R, EF-EOS R Control Ring Mount Adapter, Drop-in Filter Mount Adapter EF-EOS R EF-M lenses are not compatible⁸</td> </tr> <tr> <td>Image Stabilization</td> <td>Lens/Digital only</td> </tr> <tr> <td>Type</td> <td>Dual Pixel CMOS AF II</td> </tr> <tr> <td>AF System / Points</td> <td>With Area 100% horizontal and 100% vertical (Auto selection) 90% horizontal and 100% vertical (Manual selection)</td> </tr> <tr> <td>AF Working Range</td> <td>EV -4 – 20 (at 23°C & ISO100)²</td> </tr> <tr> <td>AF Modes</td> <td>One Shot Servo AF Auto Switch (only in A+ mode)</td> </tr> <tr> <td>AF Point Selection</td> <td>Automatic selection: 651 Available AF areas when automatically selected Manual selection: 1-point AF (AF frame size can be changed) 4503 AF positions available stills (3713 Movies) Manual selection: AF point Expansion 4 points (up, down, left, right) Manual selection: AF point Expansion surrounding</td> </tr> </table> | Form Factor | DSLR, Mirror less | Video Capture Resolution | 2160p | Lens Type | Zoom | Camera Flash | Built-In | Type | Approx. 22.3 × 14.9 mm (APS-C) CMOS | Effective Pixels | 24.2MP | Total Pixels | 25.5MP | Aspect Ratio | 3:2 | Low-Pass Filter | Built-in/Fixed | Sensor Cleaning | EOS integrated cleaning system | Type | DIGIC X | Lens Mount | RF (natively supporting RF and RF-S lenses) EF and EF-S lenses can be attached using Mount Adapter EF-EOS R, EF-EOS R Control Ring Mount Adapter, Drop-in Filter Mount Adapter EF-EOS R EF-M lenses are not compatible ⁸ | Image Stabilization | Lens/Digital only | Type | Dual Pixel CMOS AF II | AF System / Points | With Area 100% horizontal and 100% vertical (Auto selection) 90% horizontal and 100% vertical (Manual selection) | AF Working Range | EV -4 – 20 (at 23°C & ISO100) ² | AF Modes | One Shot Servo AF Auto Switch (only in A+ mode) | AF Point Selection | Automatic selection: 651 Available AF areas when automatically selected Manual selection: 1-point AF (AF frame size can be changed) 4503 AF positions available stills (3713 Movies) Manual selection: AF point Expansion 4 points (up, down, left, right) Manual selection: AF point Expansion surrounding | 01 |
| Form Factor | DSLR, Mirror less | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Video Capture Resolution | 2160p | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Lens Type | Zoom | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Camera Flash | Built-In | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Type | Approx. 22.3 × 14.9 mm (APS-C) CMOS | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Effective Pixels | 24.2MP | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Total Pixels | 25.5MP | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Aspect Ratio | 3:2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Low-Pass Filter | Built-in/Fixed | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Sensor Cleaning | EOS integrated cleaning system | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Type | DIGIC X | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Lens Mount | RF (natively supporting RF and RF-S lenses) EF and EF-S lenses can be attached using Mount Adapter EF-EOS R, EF-EOS R Control Ring Mount Adapter, Drop-in Filter Mount Adapter EF-EOS R EF-M lenses are not compatible ⁸ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Image Stabilization | Lens/Digital only | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Type | Dual Pixel CMOS AF II | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| AF System / Points | With Area 100% horizontal and 100% vertical (Auto selection) 90% horizontal and 100% vertical (Manual selection) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| AF Working Range | EV -4 – 20 (at 23°C & ISO100) ² | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| AF Modes | One Shot Servo AF Auto Switch (only in A+ mode) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| AF Point Selection | Automatic selection: 651 Available AF areas when automatically selected Manual selection: 1-point AF (AF frame size can be changed) 4503 AF positions available stills (3713 Movies) Manual selection: AF point Expansion 4 points (up, down, left, right) Manual selection: AF point Expansion surrounding | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Note: Validation of Quotation is for 6 Months.



Principal
Army Public School
Miran Sahib, Jammu

| | |
|---------------------------|---|
| | Manual selection: Flexible Zone AF 1-3 (all AF points divided into minimum 9 to 513 maximum focusing zones) Manual selection: Whole Area AF (Entire focusing area with 651 maximum focusing zones) |
| AF Tracking | Locked when shutter button is pressed halfway or AF ON is pressed in One Shot AF mode. Using customized button set to AF stop in AI servo |
| AF Assist Beam | Emitted by built in LED or optional dedicated Speedier (flash) |
| Manual Focus | Selected on lens/camera10 |
| Metering Modes | Real-time with image sensor, 384-zone metering. (1) Evaluative metering (linked to All AF points) (2) Partial metering (Approx. 5.8% of viewfinder at centre) (3) Spot metering: Centre spot metering (Approx. 2.9% viewfinder at centre) AF point-linked spot metering not provided (4) Centre weighted average metering |
| Metering Brightness Range | EV -2 – 20 (at 23°C, ISO100, with evaluative metering) |
| AE Lock | Auto: AE lock takes effect when focus is achieved (AE is locked as soon as subjects are in focus using One-Shot AF when set to [C.Fn 2: AE lock meter. mode after focus].) Manual: By AE lock button in P, Av, Fv, Tv and M modes |
| Exposure Compensation | +/-3 EV in 1/3 or 1/2 stop increments (can be combined with AEB) |
| AEB | -3 EV in 1/3 or 1/2 stop increments |
| Anti-flicker Shooting | Yes. Flicker detected at a frequency of 100 Hz or 120 Hz.11 |
| ISO Sensitivity | Auto 100-32000 (in 1/3-stop or whole stop increments) ISO can be expanded to H: 51200 |
| LCD Monitor | 7.5 cm (2.95") TFT colour LCD monitor, Approx. 1.04 million dots |
| Coverage | Approx. 100% |

2. You are requested to forward your quotation along with GST to reach this office by **20 - Oct - 2023**. The address and contact No for sending the quotations or seeking clarifications for above mentioned item are given below:

- (a) **Address:** ARMY PUBLIC SCHOOL, MIRAN SAHIB, JAMMU 181101
- (b) **Contact No:** 01923295332
- (c) **Email id:** apsmiransahib@awesindia.edu.in

Location of Tender Box: Main Gate 162 Inf Brig Miran Sahib, 181101, Jammu , Jammu and Kashmir


Principal
Army Public School
Miran Sahib, Jammu

Note: Validation of Quotation is for 6 Months.

950/3

04 Oct - 2023

CALL FOR QUOTATION

Sir/Madam,

1. Sealed quotation are invited from firm/supplier for procurement of the following items or ARMY PUBLIC SCHOOL MIRAN SAHIB:-

| S.no | Nomenclature | Specifications | Qty |
|------|--------------------|--|-----|
| 01 | DIGITAL MICROSCOPE | <p>Optical System: High Contrast finite colour corrected Optical System.</p> <p>Magnification: 40x to 1000x visual magnification</p> <p>Stand: Aluminum die-cast stand with hand rests for enhanced comfort & stability</p> <p>Observation Head: sidentopf Trinocular head, 30° inclined, 360° rotatable, Inter-pupillary distance 50-75mm, with dual dioptic adjustment.</p> <p>Eye Pieces: Widefield 10x/18mm. anti-fungal, anti-reflection, hard coated.</p> <p>Nose Piece: Reverse angle quadruple Nose-Piece (Ball bearing Type) with precise click stops</p> <p>Objectives: QUSP series high-contrast flat field DIN PLAN Achromatic objectives 4X, 10X, 40X (Spring loaded) 100X (spring loaded, oil), anti-fungal & anti-reflection hard coated.</p> <p>Mechanical Stage: Rackless X axis, Double plate stage size 190x140mm, X/Y travel range, 90mmx65mm. Low drive right hand movement controls. Hard coated surface for scratch resistance. Double specimen holder clip.</p> <p>Condenser: Sub-stage Abbe condenser NA 1.25. Iris diaphragm with frosted white/blue filter, anti-fungal anti-reflection hard coated. Rack and pinion movements on stainless steel guides</p> <p>Focusing Control: Co-axial coarse and fine focusing on gear systems for smooth operation. Fine adjustment 0.2mm/rotation with maximum 2 micron scale increment.</p> <p>Illumination: Halogen 6V-20 W or LED 3W illumination with variable illumination control. Up to 2,000 hours of Halogen Lamp life and 100,000 hours of LED life</p> <p>Electronics: Universal input 100V – 240V AC. 50/60Hz. Built in voltage stabilizer</p> <p>Package Contents: Power Cable (5ft), Immersion Oil, Spare bulb (In halogen only), Nylon Dust Cover, Cleaning Cloth,</p> <p>Accessories (Optional): Pointers & micrometer reticules, Infinity Corrected Optics, Phase-Contrast, Polarizing, Fluorescence & dark filed Kits, Quintuple nose piece, application specific objectives &</p> | 01 |

Note: Validation of Quotation is for 6 Months.


S. Sharma
Principal
Army Public School
Miran Sahib, Jammu

| | |
|-------------------|---|
| | eyepieces, Digital Cameras (3MP,9MP,10MP,14MP) & Adapters, Battery backup up to 6-7 hours, Wooden Box |
| Optical System: | High Contrast finite color corrected Optical System. |
| Magnification: | 40x to 1000x visual magnification |
| Stand: | Aluminum die-cast stand with hand rests for enhanced comfort & stability |
| Observation Head: | sidetopf Trinocular head, 30° inclined, 360° rotatable, Inter-pupillary distance 50-75mm, with dual dioptic adjustment. |
| Eye Pieces: | Widefield 10x/18mm. anti-fungal, anti-reflection, hard coated. |
| Nose Piece: | Reverse angle quadruple Nose-Piece (Ball bearing Type) with precise click stops |
| Objectives: | QUSP series high-contrast flat field DIN PLAN Achromatic objectives 4X, 10X, 40X (Spring loaded) 100X (spring loaded, oil), anti-fungal & Anti-reflection hard coated. |
| Mechanical Stage: | Reckless X axis, Double plate stage size 190x140mm, X/Y travel range, 90mmx65mm. Low drive right hand movement controls. Hard coated surface for scratch resistance. Double specimen holder clip. |
| Condenser: | Sub-stage Abbe condenser NA 1.25. Iris diaphragm with frosted white/blue filter, anti-fungal anti-reflection hard coated. Rack and pinion movements on stainless steel guides |
| Focusing Control: | Co-axial coarse and fine focusing on gear systems for smooth operation. Fine adjustment 0.2mm/rotation with maximum 2 micron scale increment. |
| Camera | Built in Camera with ULTRACAM 5.0 MP Resolution |
| Magnification | 40x to 1000x visual magnification. |
| Objectives | DIN PLAN Achromatic objectives 4X, 10X, 40X, 100X |
| Display | 12.2" TFT, IPS Touch Screen, 360° Rotatable |

2. You are requested to forward your quotation along with GST to reach this office by **20 - Oct - 2023**. The address and contact No for sending the quotations or seeking clarifications for above mentioned item are given below:

- (a) Address: **ARMY PUBLIC SCHOOL, MIRAN SAHIB, JAMMU 181101**
- (b) Contact No: **01923295332**
- (c) Email id: apsmiransahib@awesindia.edu.in

Location of Tender Box: Main Gate 162 Inf Brig Miran Sahib, 181101, Jammu, Jammu and Kashmir


Principal
Army Public School
Miran Sahib, Jammu

Note: Validation of Quotation is for 6 Months.

950/3

REGD BY E-MAIL
ARMY PUBLIC SCHOOL MIRAN SAHIB

Oct - 2023

CALL FOR QUOTATION

Sir/Madam,


1. Sealed quotation are invited from firm/supplier for procurement of the following items or ARMY PUBLIC SCHOOL MIRAN SAHIB:-

| S.no | Nomenclature | Specifications | Qty |
|------|--|--|-----|
| 01 | 4 TB Surveillance Internal Hard Drive HDD- 3.5 Inch Security Camera System with Drive Health Management, with 3 yr Warranty | Formatted capacity ⁵ 4TB Form factor 3.5-inch Advanced Format (AF) Yes RoHS compliant ⁶ Yes Product Features Cameras supported Up to 64 Drive Bays Supported 8+ AI Streams -- Firmware Feature Name All Frame 4K Tarnish resistant components Yes Performance Interface transfer rate (max) ⁵ Buffer to host 6 Gb/s Host to/from drive (sustained) 150 MB/s Cache (MB) ⁵ 64 Performance Class 5400 RPM Reliability/Data Integrity Load/unload cycles ⁷ 300,000 Annualized workload rating ⁸ 180TB/yr Non-recoverable read errors Per bits read <1 in 10 ¹⁴ MTBF 1,000,000 Limited warranty (years) ⁹ 3 | 50 |

2. You are requested to forward your quotation along with GST to reach this office by 20 - Oct - 2023. The address and contact No for sending the quotations or seeking clarifications for above-mentioned item are given below:

- (a) Address: ARMY PUBLIC SCHOOL, MIRAN SAHIB, JAMMU 181101
 (b) Contact No: 01923295332
 (c) Email id: apsmiransahib@awesindia.edu.in

Location of Tender Box: Main Gate 162 Inf Brig Miran Sahib, 181101, Jammu, Jammu and Kashmir


 Principal
 Army Public School
 Miran Sahib, Jammu

Note: Validation of Quotation is for 6 Months.